



1685 Flint Road, Toronto, ON, M3J 2W8 Canada
Tel: 416 745 9389 Fax: 416 745 0782 www.firwin.com

Fiberglass Textiles

Braided Fiberglass Sleeving

GENERAL DESCRIPTION:

Firwin Braided Sleeving is made from highly texturized Fiberglass yarn. Typical industries in which Fiberglass Sleeving is used include power generation and turbine insulation, steel, aluminum, copper and other basic metals groups, construction industry, chemical processing plants, petroleum refineries, automotive, industrial maintenance, etc.

APPLICATIONS:

Firwin Braided Sleeving provides a superior insulation cover for wiring bundles, conduit, hydraulic hoses and glass tubing.

PHYSICAL PROPERTIES:

Service Temperature: Continuous temperature to 1000°F (593°C) and higher short duration temperatures. It also withstands cold up to -100°F (-73°C).

Nominal ID	1/16" Wall (Feet/Spool)
1/4"	1400
3/8"	1400
1/2"	1000
5/8"	900
3/4"	750
7/8"	650
1"	500
1-1/4"	450
1-1/2"	350
1-3/4"	300
2"	250
2-1/2"	225
3"	200
3-1/2"	190
4"	175

* Firwin Braided Sleeving is also available in 1/8" wall thickness.